



## Material Safety Data Sheet

Copyright, 2003, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

### SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME:** 3M(TM) EXTRACTION CLEANER (Ready-to-Use) (Product No. 9, Twist 'n Fill (tm) System)

**MANUFACTURER:** 3M

**DIVISION:** Commercial Care Division

**ADDRESS:** 3M Center  
St. Paul, MN 55144-1000

EMERGENCY PHONE: 1-800-364-3577 or (651) 737-6501 (24 hours)

**Issue Date:** 06/06/2003

**Supersedes Date:** 06/08/2000

**Document Group:** 06-2711-7

**Product Use:**

Specific Use: Carpet Extraction Cleaner

### SECTION 2: INGREDIENTS

<u>Ingredient</u>	<u>C.A.S. No.</u>	<u>% by Wt</u>
WATER	7732-18-5	> 95
HYDROXY ALKYL AMINE OXIDES	68478-65-9	< 0.1
ISOPROPYL ALCOHOL	67-63-0	< 0.05
2-(2-ETHYLHEXYLOXY) ETHANOL	1559-35-9	< 0.05
DIETHYLENE GLYCOL MONO (2-ETHYLHEXYL) ETHER	1559-36-0	< 0.01

### SECTION 3: HAZARDS IDENTIFICATION

#### 3.1 EMERGENCY OVERVIEW

**Specific Physical Form:** Liquid

**Odor, Color, Grade:** Colorless, slightly hazy; pleasant fragrance.

**General Physical Form:** Liquid

**Immediate health, physical, and environmental hazards:**

#### 3.2 POTENTIAL HEALTH EFFECTS

**Eye Contact:**

Mild Eye Irritation: Signs/symptoms may include redness, pain, and tearing.

**Skin Contact:**

Prolonged or repeated exposure may cause:

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, and itching.

**Inhalation:**

Single exposure, above recommended guidelines, may cause:

Upper Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

**Ingestion:**

Gastrointestinal Effects: Signs/symptoms may include stomach upset, nausea, vomiting and diarrhea.

**3.3 POTENTIAL ENVIRONMENTAL EFFECTS**

A 3M Product Environmental Data Sheet (PED) is available.

A conservative assessment indicates this product presents a low environmental risk. Components released to the environment through use and disposal are expected to have insignificant environmental impacts.

**SECTION 4: FIRST AID MEASURES**

**4.1 FIRST AID PROCEDURES**

The following first aid recommendations are based on an assumption that appropriate personal and industrial hygiene practices are followed.

**Eye Contact:** Flush eyes with large amounts of water. Get medical attention.

**Skin Contact:** Immediately flush skin with large amounts of water. If signs/symptoms develop, get medical attention.

**Inhalation:** If signs/symptoms develop, remove person to fresh air. If signs/symptoms persist, get medical attention.

**If Swallowed:** Do not induce vomiting unless instructed to do so by medical personnel. Give victim two glasses of water. Never give anything by mouth to an unconscious person. Get medical attention.

**SECTION 5: FIRE FIGHTING MEASURES**

**5.1 FLAMMABLE PROPERTIES**

Autoignition temperature	<i>Not Applicable</i>
Flash Point	<i>Not Applicable</i>
Flammable Limits - LEL	<i>Not Applicable</i>
Flammable Limits - UEL	<i>Not Applicable</i>
OSHA Flammability Classification:	Not Applicable

**5.2 EXTINGUISHING MEDIA**

Material will not burn.

**5.3 PROTECTION OF FIRE FIGHTERS**

**Special Fire Fighting Procedures:** Nonflammable.

**Unusual Fire and Explosion Hazards:** Not applicable.

**SECTION 6: ACCIDENTAL RELEASE MEASURES**

**Accidental Release Measures:** Evacuate unprotected and untrained personnel from hazard area. The spill should be cleaned up by qualified personnel. Ventilate the area with fresh air. Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Clean up residue with water. Place in a closed container approved for transportation by appropriate authorities. Dispose of collected material as soon as possible.

In the event of a release of this material, the user should determine if the release qualifies as reportable according to local, state, and federal regulations.

## SECTION 7: HANDLING AND STORAGE

### 7.1 HANDLING

NOTE: The above precautionary information presumes that this ready-to-use product has been diluted and dispensed from a TWIST 'n FILL(TM) Chemical Dispenser. Avoid eye contact with vapors, mists, or spray. Avoid prolonged or repeated skin contact. Avoid breathing of vapors, mists or spray. Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water. Avoid contact with oxidizing agents. Keep out of the reach of children.

### 7.2 STORAGE

Store away from oxidizing agents.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 ENGINEERING CONTROLS

Use in a well-ventilated area.

### 8.2 PERSONAL PROTECTIVE EQUIPMENT (PPE)

#### 8.2.1 Eye/Face Protection

Avoid eye contact with vapors, mists, or spray.

#### 8.2.2 Skin Protection

Avoid prolonged or repeated skin contact.

#### 8.2.3 Respiratory Protection

Avoid breathing of vapors, mists or spray.

#### 8.2.4 Prevention of Swallowing

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water.

### 8.3 EXPOSURE GUIDELINES

<u>Ingredient</u>	<u>Authority</u>	<u>Type</u>	<u>Limit</u>	<u>Additional Information</u>
ISOPROPYL ALCOHOL	ACGIH	TWA	200 ppm	Table A4
ISOPROPYL ALCOHOL	ACGIH	STEL	400 ppm	Table A4
ISOPROPYL ALCOHOL	OSHA	TWA	400 ppm	Table Z-1A
ISOPROPYL ALCOHOL	OSHA	STEL	500 ppm	Table Z-1A

#### SOURCE OF EXPOSURE LIMIT DATA:

ACGIH: American Conference of Governmental Industrial Hygienists

CMRG: Chemical Manufacturer Recommended Guideline

OSHA: Occupational Safety and Health Administration

AIHA: American Industrial Hygiene Association Workplace Environmental Exposure Level (WEEL)

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

<b>Specific Physical Form:</b>	Liquid
<b>Odor, Color, Grade:</b>	Colorless, slightly hazy; pleasant fragrance.
<b>General Physical Form:</b>	Liquid
<b>Autoignition temperature</b>	<i>Not Applicable</i>
<b>Flash Point</b>	<i>Not Applicable</i>
<b>Flammable Limits - LEL</b>	<i>Not Applicable</i>

Flammable Limits - UEL	Not Applicable
Boiling point	Approximately 212 °F
Density	No Data Available
Vapor Density	No Data Available
Vapor Pressure	No Data Available
Specific Gravity	Approximately 1 [Ref Std: WATER=1]
pH	6 - 7
Melting point	Not Applicable
Solubility in Water	Complete
Evaporation rate	Approximately 1 [Ref Std: WATER=1]
Volatile Organic Compounds	< 0.2 % [Test Method: calculated per CARB title 2]
Percent volatile	> 95 %
VOC Less H2O & Exempt Solvents	No Data Available
Viscosity	<=100 centipoise

## SECTION 10: STABILITY AND REACTIVITY

**Stability:** Stable.

**Materials and Conditions to Avoid:** Strong oxidizing agents

**Hazardous Polymerization:** Hazardous polymerization will not occur.

**Hazardous Decomposition:** Under recommended usage conditions, hazardous decomposition products are not expected. Hazardous decomposition products may occur as a result of oxidation, heating, or reaction with another material.

## SECTION 11: TOXICOLOGICAL INFORMATION

Please contact the address listed on the first page of the MSDS for Toxicological Information on this material and/or its components.

## SECTION 12: ECOLOGICAL INFORMATION

### ECOTOXICOLOGICAL INFORMATION

Not determined.

### CHEMICAL FATE INFORMATION

Not determined.

## SECTION 13: DISPOSAL CONSIDERATIONS

**Waste Disposal Method:** Discharge spent solutions and small quantities (less than 5 gal.(19 L)) to a wastewater treatment system. As a disposal alternative, dispose of waste product in a facility permitted to accept chemical waste.

**EPA Hazardous Waste Number (RCRA):** Not regulated

Since regulations vary, consult applicable regulations or authorities before disposal.

## SECTION 14: TRANSPORT INFORMATION

Please contact the emergency numbers listed on the first page of the MSDS for Transportation Information for this material.

## SECTION 15: REGULATORY INFORMATION

### US FEDERAL REGULATIONS

#### 311/312 Hazard Categories:

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - No

This material contains a chemical which requires export notification under TSCA Section 12[b]:

<u>Ingredient (Category if applicable)</u>	<u>C.A.S. No</u>	<u>Regulation</u>	<u>Status</u>
ISOPROPYL ALCOHOL	67-63-0	Toxic Substances Control Act (TSCA) 4 Test Rule Chemicals	Applicable

### CHEMICAL INVENTORIES

The components of this product are in compliance with the chemical notification requirements of TSCA.

All applicable chemical ingredients in this material are listed on the European Inventory of Existing Chemical Substances (EINECS), or are exempt polymers whose monomers are listed on EINECS.

This MSDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

## SECTION 16: OTHER INFORMATION

### NFPA Hazard Classification

**Health:** 0 **Flammability:** 0 **Reactivity:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

### HMIS Hazard Classification

**Health:** 0 **Flammability:** 0 **Reactivity:** 0 **Protection:** X - See PPE section.

Hazardous Material Identification System (HMIS(r)) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS(r) ratings are to be used with a fully implemented HMIS(r) program. HMIS(r) is a registered mark of the National Paint and Coatings Association (NPCA).

DISCLAIMER: The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M.

3M MSDSs are available at [www.3M.com](http://www.3M.com)