



Pacer 214 UE | 218 UE

14" and 18" Two-Motor Upright Vacuums



For quick, effective carpet vacuuming, the Pacer 214 UE and Pacer 218 UE combine cleaning power and ease of operation to make them the ideal choice in two-motor uprights.

- One motor for suction power and a second motor to drive the brush for the most effective cleaning performance.
- Ergonomic design features reduce operator fatigue.
 - Enclosed ergonomic handle allows a relaxed grip.
 - Large built-in carrying handle makes transport easy.
- 3-stage filtration system enhances IAQ.
 - Poly-lined two-ply paper filter bag contains the vacuumed dirt.
 - Stage-two motor filter provides added filtration in the event of a tear in the filter bag.
 - Exhaust filter traps additional particles and carbon brush dust created by the vacuum motor.
- Brush motor shuts off when the wand is in use for detail cleaning, protecting the carpet from brush burn.
- Removable suction tube makes clearing clogs simple.

NSS Enterprises, Inc.
3115 Frenchmens Road
Toledo, Ohio 43607-2958
USA
www.nss.com



Pacer 214 UE / 218 UE Specifications

Brush	Spiral brush with replaceable strips	Switches & Controls	Rocker on/off switch and bag full indicator light	Dimensions -Height	48.75 in. (125 cm)
Vacuum Motor -Type -Flow -Waterlift	2-stage, 10.5 amps @ 120V. (1000 watts) 4.4 amps @ 240V. (1000 watts) 91 CFM 84-in.	Cord	40-ft. (12.2 m) 18-3 SJT safety yellow	-Width	•214 UE 14.5 in. (36 cm) •218 UE 18.5 in. (46 cm)
		Construction	High-impact ABS plastic	-Weight	•214 UE 21 lbs. (9.5 kg) •218 UE 22 lbs. (10 kg)
Brush Motor	1.4 amps @ 120V. (150 watts) 0.8 amps @ 240V. (150 watts)	Sound Level -214 UE -218 UE	65 dbA 66 dbA	-Shipping	•214 UE 27 lbs. (12.5 kg) •218 UE 28 lbs. (13 kg)
		Capacity	5 quarts dry (4.75 liters)	Warranty	1 year limited 2 years on motors and PC board
Filtration	3-Stage—Top-filled, two-ply poly-lined filter, motor, and exhaust filter. Micro optional.	Cleaning Path -214 UE -218 UE	14 in. (36 cm) 18 in. (46 cm)		
Productivity — Floor coverage for the Pacer 214 UE is 4,000 sq. ft. per hour (372 m ²), and floor coverage for the 218 UE is 5,130 sq. ft. per hour (465 m ²).					

3-Stage Filtration



1) Top-filling, poly-lined two-ply paper filter.



2) Motor filter.



3) Exhaust filter.

1 Built-in two-piece suction wand and on-board tools simplify detail cleaning.

2 On-board lighted on/off switch.

3 Built-in carrying handle for easy transport.

4 High-impact ABS plastic for long life.

5 Wrap-around, non-marking bumper protects furniture and walls.



11 Enclosed, ergonomic handle allows the operator to vacuum with a relaxed grip.

10 Cord strain relief prevents damage to the cord due to accidental pull-out.

9 40-ft. cord reduces outlet changes.

8 Bag full indicator light activates when bag needs changing or vacuum chamber is clogged.

7 Easy access to brush housing for quick brush strip changes.

6 Pacers clean right to the edge, right up against the wall.



NSS® Enterprises, Inc.
3115 Frenchmens Road
Toledo, Ohio 43607-2958 USA
419/531-2121 or 800/677-1663
Fax 419/531-3761
www.nss.com
mailto:mailus@nss.com
Specifications and machine appearance
subject to change without notice.

DISTRIBUTED BY